



## Example of possible Product specification

### FIBRON PS LF LOW-FLUX Membrane

Synthetic hollow fiber membrane bundle acc. Customer´s specification

	Unit	Value	Tolerance
<b>Membrane</b>			
Type		Low flux membrane	
Name		FIBRON PS LF	
Material		Polysulfone FIBRON AG Spec.	
Wall thickness	µm	40	±7
Inner diameter	µm	200	±15
Hydraulic permeability	ml/(h m <sup>2</sup> mmHg)	17	±3,0
Diffusive permeability	10 <sup>-3</sup> cm/min		
		<i>creatinine</i>	55 ±15
		<i>vitamine B<sub>12</sub></i>	12,0 ±3,5
Burst pressure	bar	>4	

#### Bundle

Acc. Dialyzer Housing dimensions

Number of fibers		Acc. Customer	±100
Length (inside dialyser)	mm	Acc. Customer	±1
Diameter (incl. wrap)	mm	Acc. Customer	<sup>-2</sup> / <sub>+1</sub>
Wrap		PE-sheet	

#### Packaging

Bundles per package	Acc. Customer
Packaging	non sterile, double – single welded – PE-bag in carton

Lifetime of FIBRON AG products: 2 years plus 3 years in dialyzers, manufactured by validated standardised procedures certified according to international standards.

Non-warranty clause: FIBRON AG and insurer of FIBRON AG disclaim liability for FIBRON AG products including dialyzers containing FIBRON AG products not single tested regarding integrity and put into the USA and Canada market.

FIBRON AG reserves the right to alter any parameter of the specification mentioned above.